

TEHNIČKI PODACI	JEDINICE	DD-11-GOLD ET2	DD-14-GOLD ET2	DD-18-GOLD ET2	DD-22-GOLD ET2	DD-28-GOLD ET2	DD-35-GOLD ET2	DD-45-GOLD ET2	DD-60-GOLD ET2	DD-80-GOLD ET2
--------------------	----------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------	-------------------

Kapacitet 1:18 / 1:20	kg	11,7/10,5	15/13,5	18,3/16,5	24,3/21,9	30,5/27,5	36,6/33	49,8/44,8	66,8/60,1	83,3/75
Izlaz po satu (el.ektr./gas)	Kg/h	21,7/31,3	29/32,5	30,3/33,6	40/44,6	51,6/61,1	63,9/73,3	90/96	128,6/144	136,4/187,5
Kapacitet isparavanja (elektr./gas)	l/h	11/15	14,5/15,6	14,9/16,3	20/22,3	26,8/31,8	31,5/34,7	45/48	64/72	68,2/93,8

Ø Bubanj	mm	750	750	750	835	947	947	1225	1225	1225
Ø Vrata	mm	574	574	574	574	802	802	802	802	802
Visina centra vrata	mm	976	976	976	1030	1040	1040	1275	1275	1275
Visina osnove vrata	mm	689	689	689	743	640	640	874	874	874
Dužina bubnja	mm	475	610	746	800	780	936	760	1020	1252
Zaprem ina bubnja	l	210	269	330	438	549	659	896	1202	1500

SNAGA

Snaga motora bubnja	kW	0,37	0,37	750	835	0,55	0,55	0,75	1,1	1,5
Snaga motora ventilatora	kW	0,55	0,55	574	574	0,75	0,75	2,2	2,2	2,2
Snaga grejanja na struju	kW	12	18	976	1030	30	36	54	72	72
Ukupna električna snaga (elek. model)	kW	12,97	18,97	689	743	31,35	37,35	57	75,35	75,75
Snaga grejanja na gas	kW	20,51	20,51	746	800	41	41	60	90	120
Trenutna potrošnja propana (G31)	kg/h	1,76	1,76	330	438	3,51	3,51	5,14	7,71	10,28
Trenutna potrošnja propana (G20)	m3/h	2,17	2,17	2,17	3,28	4,34	4,34	6,35	9,53	12,71
Ukupna električna snaga (gasni model)	kW	0,97	0,97	0,97	1,17	1,35	1,35	3	3,35	3,75
Snaga parnog grejanja	kW	30	30	30	49,2	50,1	50,1	91,3	128	128

Ukupn a elektr ična snaga (parni model)	kW	0,97		0,97		0,97		1,17		1,35		1,35		3		3,35		3,75	
POVEZIVANJE		ELEKTRIČNOGA S/PARA		ELEKTRIČNOGA S/PARA		ELEKTRIČNOGA S/PARA		ELEKTRIČNOGA S/PARA		ELEKTRIČNOGA S/PARA		ELEKTRIČNOGA S/PARA		ELEKTRIČNOGA S/PARA		ELEKTRIČNOGA S/PARA		ELEKTRIČNOGA S/PARA	
Napon 230V- I+N+T	N ^o x mm2/A	3×25/ 63A	3×1,5/ 20A	-	3×1,5/ 20A	-	3×1,5/ 20A	-	3×1,5/ 20A	-	3×1,5/ 20A	-	3×1,5/ 20A	-	-	-	-	-	-
Napon 230V- III+T	N ^o x mm2/A	4×10/ 40A	3×1,5/ 20A	4×16/ 63A	3×1,5/ 20A	4×16/ 63A	3x1,5/ 20A	4x25/8 0A	3x1,5/ 20A	4x35/1 00A	3x1,5/ 20A	4x50/1 25A	3x1,5/ 20A	-	4x2,5/ 20A	-	4x2,5/ 32A	-	4x2,5/ 32A
Napon 400V-II I+N+T	N ^o x mm2/A	5×4/2 5A	3x1,5/ 20A	5×10/ 32A	3x1,5/ 20A	5×10/ 32A	3x1,5/ 20A	5×10/ 32A	3x1,5/ 20A	5×10/ 40A	3x1,5/ 20A	5×16/ 63A	3x1,5/ 20A	5×35/ 100A	5x1,5/ 20A	5×50/ 125A	5×1,5/ 32A	5×50/ 125A	5×1,5/ 32A
Ø Ulaz za gas	BSP	1/2"		1/2"		1/2"		1/2"		1/2"		1/2"		3/4"		3/4"		3/4"	
DIMENZIJE / DIMENZIJE PAKOVANJA																			
Neto širina / Bruto širina	mm	785/865		785/865		785/865		890/970		985/1065		985/1065		1.270/1.330		1.270/1.330		1.270/1.330	
Neto dubina / Bruto dubina	mm	855/940		989/1.074		1.125/1.210		1.255/1.345		1.054/1.154		1.210/1.310		1.106/1.185		1.366/1.455		1.598/1.705	
Neto visina / Bruto visina	mm	1.694/1.840		1.694/1.840		1.694/1.840		1.812/1.940		1.975/2.080		1.975/2.080		2.380/2.150		2.380/2.150		2.380/2.150	
Visina bez grejača	mm	-		-		-		-		-		-		1.950		1.950		1.950	
Neto težina / Bruto težina	Kg	172/180		180/190		187/200		210/230		230/260		260/285		395/430		529/575		657/715	

OSTALO										
Maksimalni protok vazduha	m3/h	1.200	1,2	1.200	1.500	1.500	1.500	4,5	4,5	4,5
Ø Izduv vazduha	mm	200	200	200	200	200	200	300	300	300
Nivo buke	dB	64	64	64	65	65	65	67	67	67